

IBX-100


Fanless AMD® Geode LX / GX Embedded System



Features

- ◆ IBX-100-GX2's memory onboard design ideal for robust operating environment
- ◆ Built-in 802.11b/g wireless with PIFA antenna
- ◆ Supports one 2.5" hard drive and one CompactFlash
- ◆ Rear-accessible CompactFlash slot with plastic cover protected

Fanless




Specifications

Model No.	IBX-100-LX2	IBX-100-GX2
SBC Inside	NANO-LX2	NANO-GX2
CPU	AMD® Geode LX-800 500MHz	AMD® Geode GX-466 333MHz
Chipset	CS5536	CS5536
System Memory	One 200-pin 333/400MHz DDR SDRAM SO-DIMM supported (system max. 1GB)	128MB / 256MB DDR266 onboard
Ethernet	Two 10/100Mbps RTL8100C Ethernet Controllers	One 10/100Mbps RTL8100C Ethernet Controllers
Wireless	Built-in 802.11b/g mini PCI module	
Display	CRT interface integrated in AMD® Geode LX800, with one VGA port	CRT interface integrated in AMD® Geode GX466, with one VGA port
USB	Two USB 2.0 ports	
Serial Port	Two RS-232	
Storage	One CompactFlash slot and one 2.5" IDE hard drive	
Power	5VDC input with 25W AC-DC adaptor	
Operating Temperature	0°C ~45°C	
Operating Vibration	MIL-STD-810F 514.5C-1 (with hard drive) MIL-STD-810F 514.5C-2 (with CompactFlash)	
Operating Shock	Half-sine wave shock 3G; 11ms; 3 shocks per axis	
Weight (Net/Gross)	880 g / 2.1 kg	
Dimensions (DxWxH)	150.8 mm x 185.9 mm x 49.4 mm	

Dimensions

unit: mm



Ordering Information

Part No.	Description
IBX-100-GX2-R10/128MB	Embedded system with AMD® Geode GX466 333MHz CPU, 128MB DDR memory onboard, built-in 802.11b/g wireless, 5VDC in, with 25W adaptor, white
IBX-100-GX2-R10/256MB	Embedded system with AMD® Geode GX466 333MHz CPU, 256MB DDR memory onboard, built-in 802.11b/g wireless, 5VDC in, with 25W adaptor, white
IBXCF-100-GX2-CE	OS Image with WINCE, for IBX-100-GX2, with Compact Flash Memory Card 128MB, RoHS
IBXCF-100-GX2-XPE	OS Image with Windows XPE, for IBX-100-GX2, with Compact Flash Memory Card 1GB, RoHS

Part No.	Description
IBX-100-LX2-R10/256MB	Embedded system with AMD® Geode LX800 500MHz CPU, built-in 802.11b/g wireless, 256MB DDR memory, 5VDC in, with 25W adaptor, white, RoHS
IBXCF-100-LX2-CE	OS Image with WINCE, for IBX-100-LX2, with Compact Flash Memory Card 128MB, RoHS
IBXCF-100-LX2-XPE	OS Image with Windows XPE, for IBX-100-LX2, with Compact Flash Memory Card 1GB, RoHS